

EQUIPCOAT™

Keep Equipment Looking Its Best!

Specifications

DESCRIPTION

EQUIPCOAT™ is a crystal clear polymeric plastic resin that can last for years and can significantly increase resale value. EQUIPCOAT™ reduces maintenance & cleaning. Prevents rusting and restores faded paint. Coated surface cleans up easily with just soap & water. EQUIPCOAT™ will not chalk, crack, peel or yellow. A two-coat system should be applied when equipment is used in a chemically exposed environment.

*Not for use on glass or plastic mirror lens.

Equipcoat™ Protective Coating: for

- Formulated for use on Heavy Construction Equipment & School Buses
- Recommended for use by experienced applicators.
- Long-Term protection helps prevent rust, corrosion & oxidation.
- Seals - Polymer resin encapsulates metal surfaces.
- Crystal Clear Coating - will restore paint gloss and enhances color.
- Highly Corrosion Resistant. EquipCoat protects equipment from, U.V., road salt, calcium chloride, phosphates, fertilizer, urea, damage, etc.
- Use on new and used equipment.
- Fast Drying
- Heat resistant- Allows coating of radiator, engine & their components.
- Help prevent corrosion on wire harnesses
- Indefinite Shelf Life in a closed container.
- Will not chip, crack, peel or yellow when applied as directed.
- Will bond to itself - No sanding or priming needed to apply or when reapplying.
- Paintable- touchup paint or apply numbers
- Reduces paint damage on leased and rental equipment
- Reduces Maintenance – Coated Surfaces are slower to dirty, easier to clean. EquipCoat is a Highly Cleansable Surface.
- Economical – thoroughly coat a large school bus with just 2 quarts

Properties

PROPERTIES	METHOD	UNITS	SPECIFICATION
Appearance	D4176	-	Clear & Free From Impurities (<i>colorless liquid</i>)
Color	D156 D1209	Saybolt PT-Co	N/A
Odor	-	-	AROMATIC
Density @ 20°C	D1298	lb./gal	7.8
Boiling Point	D86	-	182°C
Melting Point	-	-	<450°F
Flash Point	-	-	155°F TCC
Dielectric	D877	kV	38.1
Vapor Pressure	¹	mm Hg	5 @ 40°C
Vapor Density		-	>Air
Aniline Point	D611	-	< -3°C
Solubility in Water	-	-	Insoluble
Viscosity	-	-	31.5 Zahn #2
V.O.C.	-	g/L	679 g/L 48 g/L formula available
Kauri Butanol	D1133	-	60

1. Head Space Gas Chromatography
2. Methods - ASTM

Packaging/Sizes

SIZES:

Equipcoat™ Protective Coating: is available in Quart and Gallon sizes.

COVERAGE:

Quart - approx. 250 sq. ft

Gallon - approx. 1000 sq. ft

Aerosols 12oz - approx. 60 sq. ft

EVERBRITE INC.

Sales: 916-852-0200

www.Equipcoat.com

over



EQUIPCOAT™

Keep Equipment Looking Its Best!

Application Data

SURFACE PREPARATION

Remove all wax, cosmolian, grease, road tar, and oxidation. Remove rust, dead or loose paint and any peeling clear-coat. Wash equipment with EquipCoat cleaners or another free-rinsing detergent, rinse thoroughly and allow to dry completely. **RINSE THOROUGHLY – DO NOT ALLOW THE CLEANERS TO DRY ON THE SURFACE.**

APPLICATION

Provide adequate ventilation & remove all sources of ignition or sparks. Do not apply to hot metal or the coating will not self-level before it dries. Apply a single coat that thoroughly wets the surface. Allow drying. Use two coats for rust and corrosion protection. Apply EQUIPCOAT™ with automotive type paint sprayer using a fine finish tip, a small microfiber roller or wiping pads may be used to cut in window frames, handrails, mirror brackets, etc. Under warm and dry conditions EquipCoat will dry to the touch in 15 to 30 minutes. Allow 24-48 hours curing time before using coated equipment in a corrosive environment.

AFTER CARE

Coated surface cleans up easily with just soap & water. Use a fireman hose or pressure washer with a fan tip. Do not use degreasing soaps or any solvent based cleaners.

Health & Safety

CAUTION

Combustible liquid. Do not smoke or use near flame. Use with adequate ventilation. Avoid continuous breathing vapor or spray mist. When spraying, wear NIOSH approved respiratory mask. Avoid prolonged contact with skin. Store in cool, dry place.

FIRST AID

DANGER: HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN. First Aid: In case of eye contact, flush thoroughly with plenty of water for 15 minutes and get medical attention. For skin contact, wash with soap and water. In case of respiratory difficulty, provide fresh air and call a physician. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with damage to health. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Read all directions and cautions on MSDS. This product sold without warranty as to performance expressed or implied. Users are urged to conduct their own test to determine the suitability for their particular conditions.

DISPOSABLE PROCEDURES

Disposal should be in accordance with local, regional or national regulations. Contaminated waste and packaging should be destroyed by incineration at an approved incinerator. If recovery of contaminated product is not possible, it should be destroyed by incineration.

Shipping & Handling

SHIPPING NAME:US DOT – Not Regulated.
Hazard Class.....N/A
Identification NumberN/A
Packing Group.....N/A
Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

WARRANTY: The statements made herein, on labels, product bulletins, or by any of Everbrite Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Everbrite's control in application, surface preparation, surface temperature, humidity and other variable factors Everbrite assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Everbrite or its agents constitutes acceptance of the terms of this warranty. In the event that Everbrite finds that the product delivered is not of Everbrite's standard quality, Everbrite will at its sole discretion, either replace the product or refund the purchase price. Everbrite's choice of one of these remedies shall be the Buyer's sole remedy. Everbrite will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Everbrite will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control. (07/11)
EVERBRITE, INC. 11492 Sunrise Gold Circle Rancho Cordova, CA 95742 • Tel: 916-852-0200 • www.Equipcoat.com.